



# Model | TGO-33~TSL01

TrueGO Glass Door Merchandiser



Payment systems  
sold separately.

ROUGH-IN DATA			(Specifications subject to change without notice. Chart dimensions rounded up to the nearest 1/8" (millimeters rounded to the next whole number).)									
Model	Doors	Shelves	Cabinet Dimensions (in/mm)			HP	Voltage	Amps	NEMA Configuration	Cord Length (ft./m)	Crated Weight (lbs./kg.)	
			W	D*	H							
TGO-33~TSL01	1	6	33 <sup>3</sup> / <sub>16</sub>	29 <sup>7</sup> / <sub>8</sub>	78 <sup>21</sup> / <sub>32</sub>	1/3	250/50/1	2.4	Varies	Varies	450	
			840	759	1998	n/a	—	n/a	—	—	204	

\*Depth does not include 1 5/8" (42 mm) for door handles.

## Standard Features

- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), and three (3) global warming potential (GWP).
- Energy efficient, factory balanced, refrigeration system holds 33°F to 38°F (.5°C to 3.3°C) cabinet temperature.
- Exterior- non-peel or chip, black powder coated, cold rolled steel; durable and permanent.
- Interior- attractive, NSF approved, white aluminum interior liner with stainless steel floor.
- Self closing door. Positive seal, torsion type closure system.
- "Low-E", double pane, thermal insulated glass door assembly with extruded aluminum frame. The latest in energy efficient technology.
- LED interior lighting provides more even lighting throughout the cabinet. Safety shielded.
- Entire cabinet structure is foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).

## Options

- 4" castor, 2½" castor, price strips.

## TrueGO Features

- TrueGo is the future of self-contained, unattended retail. Sell any products anywhere, anytime. No cashiers. No lines. Unlimited sales. Simply swipe, take what you want, and close the door.
- The TrueGO allows the consumer the experience of touching the product and reading product information before the purchase.
- The TrueGO comes ready to use, and easily connects via WiFi, Ethernet, or cellular to get you up and running fast.
- Standard with 5 shelves, with 4 weighted scales per shelf. Allows for up to 20 different SKUs per unit.
- Each scale can hold up to 35 lbs., allowing for very few product restrictions.
- Integrated Health Safety Lock will automatically lock the unit if the internal temperature stays above 41°F for 30 minutes.

## Software

- Simple to use ShelfX software allows for purchase tracking, inventory manage-

ment, and the ability to track changes. Sales summary reports make it easy to manage your new unattended retail business.

- Product flexibility and pricing are easily adjustable, and can accompany any request such as combo deals or special privileges for employees, encouraging multi-product transactions.
- The TrueGo set up process is easily customizable and can be done from anywhere, including your laptop, iPad, and iPhone or Android device.

## Payment Systems

- TrueGO can accept many payment solutions including all credit and debit cards, Apple Pay, employee cards/IDs and XCards (by ShelfX).
- Supports card readers from USA Technologies and NAYAX.
- Payment systems are sold separately.

## True Warranty

- True offers a 3 year parts and labor warranty along with an additional 2 year warranty on the compressor.

## ShelfX Warranty

- ShelfX parts are covered by a 90 day warranty. This includes part such as scales, sensors, boards, and connections.



115/60/1  
NEMA-5-15R



## PLAN VIEWS

